


50% Special Study Objective, Scope and Methodology

Performed as part of 2016-2017 Transmission Planning Process


Sushant Barave June 20, 2016



Objective of the 50% special study


- ☐ Continue investigating the <u>transmission impacts</u> of moving beyond 33% assuming procurement based on
 - i. Deliverability Status Energy Only (EO) or Full Capacity (FC)
 - ii. Resource location In-state or Out-of-state
- □ Test the <u>transmission capability estimates</u> used in RPS calculator v6.2 and update these for the next release of RPS calculator
- Strictly an informational effort
 - will <u>not</u> provide basis for procurement/build decisions in 2016-17 TPP cycle
 - Will be used to develop portfolios for consideration by CAISO in future TPP cycles
- Coordination with regional planning entities for the out-of-state portfolio modeling and assessment

50% Special study timeline (in 2015-2016 planning cycle)




A brief look at the portfolios – In-State

In-State FCDS (New MW Capacity) ~14,877 MW



In-State EO (New MW Capacity) ~14,848 MW




■ Biogas ■ Biomass ■ Geothermal ■ Hydro ■ Solar PV ■ Solar Thermal ■ Wind




A brief look at the portfolios – Out-of-state


Out-of-State FCDS (New MW Capacity) ~11,127 MW



Out-of-State EO (New MW Capacity) ~11,127 MW










Study Scope and Sequence

- Four portfolios will be studied
 - i. In-state EO
 - ii. In-state FC
 - iii. Out-of-state EO
 - iv. Out-of-state FC
- □ Resource mapping for each portfolio
- Production cost simulations
- Identification of high transmission utilization snapshots from 8,760 Hrs data from production cost simulations
- Reliability studies (Power flow, post-transient, transient stability)
- Deliverability assessment





- Resource mapping used the information from the existing ISO queue and geographical information provided by CPUC
- Deliverability assessment to be performed only for the FCDS portfolios
- Production cost simulation output is used to
 - Inform power flow cases (generation dispatch and major path flows)
 - Give information about renewable curtailment
- ☐ Reliability assessment will involve identification of constraints that
 - May limit considerable amount of generation
 - Would need expensive upgrades
- ☐ Such constraints will form the basis for the transmission inputs to the RPS calculator for future use



Expected outcomes and next steps

Expected outcomes:

- Impacts of FCDS resource build-up beyond 33% main incremental effort over the previous study (In-state and Out-of-state futures)
- ☐ Identification of transmission limitations that would prohibit EO or FC interconnection of a large amount of resources in any renewable zones.
- ☐ Extent of renewable curtailment (overall vs. estimation of curtailment caused by transmission congestion)
- □ Refinement to the transmission capability estimates to be used for creating future renewable portfolios

Next Steps:

- Resource mapping and modeling of portfolios
- Production cost modeling and simulation
- An update at the TPP Stakeholder Meeting #3 (November 2016)
- Feedback to the CPUC (February 2017)

Questions?